

PROPOSAL FOR CODE CHANGE

State Form 41186 (R3 / 5-10)

JAN **1 8** 2019

RECEIVED IDHS

COMMISSION STAFF

INSTRUCTIONS:

Change to read as follows

- 1. Only a TYPED copy will be accepted.
- Dashed line through material to be deleted. <u>Underline</u> or bold face material to be added.
- 3. Use a second sheet for any material requiring more space.
- 4. Return this completed form to: Indiana Department of Homeland Security, Code Services, 402 West Washington Street, Room W246, Indianapolis, Indiana 46204.



FOR OFFICE USE ONLY							
Received 1/18/2019	Code 2018	IRC	Proposal number # 379				
Code title: Indiana Residential Code			Edition 2020				
Section number and title R408.3 Unvented crawl space	Page Number 1 of 1, Codebook page 133						
Proponent Representing (if applicable)			e)				
Craig Wagner IABO for 2.1 and 2.2, SIBA			, SIBA for 2.4				
Address (number and street, city, state, and ZIP code)			Telephone number				
220 W Van Buren St, Ste 204, Columbia City, IN 46725			(260) 248-3111, cell 260-212-2943				
PROPOSED CODE CHANGE (check one)							

Delete without substitution

Section R408.3, delete item 2.1, 2.2 and 2.4, and substitute as follows (Item 2.3 is not amended by this proposal):

Add to read as follows X Delete and substitute 2.1, 2.2 and 2.4 as follows

- 2.1. The walls of the under-floor space are insulated in accordance with Chapter 11 and Section R316 of this code. Uninsulated mechanical ductwork is allowed and shall have no openings into the under-floor space. A hard surface pad with dimensions of at least 16 inches (407 mm) by 16 inches (407 mm) and an electrical receptacle shall be located adjacent to the sump or gravity drain to allow for the installation of dehumidification equipment in the event of high humidity conditions in the under-floor space.
- 2.2. The walls of the under-floor space are insulated in accordance with Chapter 11 and Section R316 of this code with insulation materials listed for the interior of a dwelling, or the materials shall be protected in accordance with their listing. A concrete floor at least 2 inches (51 mm) thick installed over a vapor retarder complying with Item 1. of this section shall be installed on the ground surface of the under-floor space. Conditioned air shall be circulated through the under-floor space at a rate of at least 1 cfm (0.03 m³) for each 50 square feet (4.6 m²) of under-floor space.
- 2.4 Construction of the crawlspace area shall be in accordance with Section R703.8.6 and Figure R703.8.6(1). The crawlspace perimeter walls are insulated in accordance with Chapter 11 and Section R316 of this code, and insulated or uninsulated ductwork supplies conditioned air to the crawlspace area.

REASON STATEMENT AND FISCAL IMPACT

This proposal, revised 12-27-2018, reflects the language in our current rule and gives direction for installation of crawl spaces for dwellings. Revisions to the original proposal #125 include;

- 1. The words "Ventilation openings are not required when" were struck by amendment in committee on 7-18-18.
- The references to Section R314 were incorrect, that section in the 2018 IRC is for smoke detectors, the foam insulation sections have been combined into Section R316 in the 2018 IRC.
- 3. Exception #5 from Section R408.2 of 2005 InRC was not brought forward in the original proposal and is added to this amended proposal at the request of the Southwestern Indiana Builders Association.

Fiscal impact: This proposal is fiscally neutral with the 2018 IRC.

	RECEIVED 1043				
	REVIEW RECO	OMMENDATION			
Approve	TION AT VINC				
	- COMWISSION				
Reject	And the second s			-	
Approve as amended			1 7		
Further study					

PROPOSAL FOR CODE CHANGE

State Form 41186 (R3 / 5-10)

JAN 25 2019

RECEIVED

COMMISSION STAFF

INSTRUCTIONS:

- Only a TYPED copy will be accepted.
- 2. Dashed line through material to be deleted. <u>Underline</u> or bold face material to be added.
- 3. Use a second sheet for any material requiring more space.
- 4. Return this completed form to: Indiana Department of Homeland Security, Code Services, 402 West Washington Street, Room W246, Indianapolis, Indiana 46204.



FOR OFFICE USE ONLY							
Received 1/25/2019	2018	IRC	Proposal number # 380				
Code title Indiana Residential Code	,		Edition 2020				
Section number and title			Page Number				
R507.4.1 Deck post to deck footing connect	1 of 1, codebook page 163						
Proponent	(Representing (if applicable					
Craig Wagner	x x	IABO					
Address (number and street, city, state, and ZIP code)		/	Telephone number				
220 W Van Buren St, Columbia City, IN 467			260-248-3111				
	PROPOSED CODE (CHANGE (check one)					
R507.4.1 Deck post to deck footing connection. Where posts bear on concrete footings in accordance with Section R403 and Figure R507.4.1 R507.3, lateral restraint shall be provided by manufactured connectors or a minimum post embedment of 12 inches (305 mm) in surrounding soils or concrete piers. Other footing systems shall be permitted. Exception: Where expansive, compressible, shifting or other questionable soils are present, surrounding soils shall not be relied on for lateral support.							
This proposal references the correct table number.							
Fiscal impact: none REVIEW RECOMMENDATION							
Approve	REVIEW RECO	WINENDATION					
Reject							
Approve as amended		,					
Further study							